



THE MUD STOPS HERE.

REUSABLE CONSTRUCTION ENTRANCE




1-844-200-3637 | www.getfods.com

PERFORMANCE & BENEFITS

FODS Reusable Construction Entrances outperform traditional rock and geofabric stabilized construction entrances, and can be installed in under 30 minutes and configured to any entrance detail.


Our Trackout Control Mats were engineered to deform tires as vehicles pass over, without damage to the tire. Rows of staggered pyramids effectively dislodge sediment, stone and debris. The debris is collected into the base of each mat and will not come in contact with the tires of subsequent vehicles. As a rockless system, it mitigates the hazards of aggregate being lodged in vehicle tires and transported into traffic. FODS improves environmental compliance by reducing construction site track out onto roadways.



Pyramids effectively clean tires through compression and stretching without damage to the tire




Built-in ramp for gradual transition onto and off of mats



Improves compliance, prevents road hazards

SPECIFICATIONS

Mat Size: 12'(w) x 7'(l) x 3 3/4"(h)
 Pyramid Size: 2 7/8"(h)
 Mat Weight: 420 lbs.
 Lifespan: 10+ years



Passenger vehicles easily traverse the FODS System



Mats are simple to stack and transport from worksite to worksite

FODS VS TRADITIONAL SCE

FODS Reusable Construction Entrances:

- ✓ Avoid labor and time intensive processes for each project
- ✓ Mats are engineered for reusability and ease of use
- ✓ Mats handle over 1,000,000 passes of an 80,000 lb vehicle
- ✓ Mats have a lifespan of 10+ years

Traditional Construction Entrances:


- ✗ Require 80-100 tons of rock to build
- ✗ Entrance fills with mud and must be refreshed by hauling in additional stone
- ✗ All contaminated waste must be sent to a landfill afterwards



NUMBER OF TRUCKS USED PER ENTRANCE INSTALLATION & REMOVAL



Mats can be installed and anchored to any substrate





Harris County Field Trial

With our experience with the system (FODS) we observed that it cut the amount of street sweeping we had to perform by half on rainy and dry days. All in all, Challenger had a very positive experience using FODS and would definitely recommend them to other contractors.

- Zach Parker, Challenger Texas

60%

Reduction in construction site trackout

89%

Reduction in maintenance of construction site entrance



Mats are Made In the USA with 100% USA Sourced Materials



INSTALL IN

30

MINUTES



CRUSH RATING

2.8

MILLION IBS.



LIFE SPAN

10+

YEARS

INDUSTRIES



Energy & Natural Resources



Residential & Mixed Use



Highway, Bridge & Heavy Civil




Aviation & FOD Prevention


VERSATILE MAT LAYOUTS




1x4




2x4



1x4T



1x5T



1x7T

CLEANING & MAINTENANCE

To ensure maximum system performance, FODS mats should be inspected and maintained as necessary. Mats should be cleaned once voids between the pyramids fill up with 2.5 inches of sediment above the base of the mat. Cleaning methods vary depending on soil type and available equipment.

Cleaning Methods:


- FODS Shovel
- Skid-Steer Broom Attachment (enclosed broom for dust control)
- Street Sweeper (requires adjustable bristle head)
- Pressure Washer (must have ability to contain water)
- Water Truck (must have ability to contain water)



Buildup Before



After Cleaning



Cleaning Direction



FODS Shovel



REUSABLE CONSTRUCTION ENTRANCE

7382 S Revere Pkwy #204B, Centennial, CO 80112

303-395-1069 or TOLL FREE 1-844-200-3637

www.getfods.com | info@getfods.com



100%
Recyclable
HDPE