



TRACKOUT CONTROL MATS

PATENT# US 8,061,927 B1

SHIPPING GUIDE

FODS TRACKOUT CONTROL MATS

Designed to reduce trackout and maintain cleaner site exits across construction, energy, and infrastructure projects. FODS Trackout Control Mats provide a durable, reusable solution optimized for consistent performance and efficient shipping.

MAT SPECIFICATIONS

Mat Dimensions: 12' W × 7' L × 3.75" H (3.7 m × 2.1 m × 95 mm)

Mat Weight: 420 lbs (190 kg)

Pallet (8 nested mats): 12' W × 7' L × 24" H (3.7 m × 2.1 m × 0.61 m), 3,500 lbs (1,590 kg)

MATERIAL

High Density Polyethylene (HDPE) with 15-year UV inhibitor

Flammability: Highly Resistant (UL94HB)

LOAD CAPACITY

Per Pyramid: 22,000 lbs (9,979 kg) to Initial Deformation

Per Pyramid: 48,000 lbs (21,772 kg) to Ultimate Crush

SHIPPING INFORMATION

20' Container: 36 mats & accessories

40' Container: 108 mats & accessories

Standard 48 ft flatbed: 96 mats (12 pallets)

FODS Mats HS Code: 3926.90

NEED HELP PLANNING A SHIPMENT?

For project-specific recommendations, container optimization, or international shipping support, contact the FODS team.

getfods.com
1-844-200-3637



GROUND PROTECTION MATS

PATENT# US 8,061,927 B1

SHIPPING GUIDE

GROUND PROTECTION MATS

Designed for temporary access and ground stabilization across construction, energy, and infrastructure projects. FODS Ground Protection Mats provide a lightweight, durable solution optimized for efficient transport and high-volume shipping.

MAT SPECIFICATIONS

Mat Dimensions: 8' L × 4' W × 0.5" H (2.4 m × 1.2 m × 12.7 mm)
7/8" (22 mm) with mat tread pattern

Mat Weight: 88 lbs (40 kg)

20-Mat Pallet: 8' L × 4' W × 24" H (2.4 m × 1.2 m × 0.61 m), 1,850 lbs (840 kg)

30-Mat Pallet: 8' L × 4' W × 32" H (2.4 m × 1.2 m × 0.81 m), 2,750 lbs (1,250 kg)

MATERIAL

High Density Polyethylene (HDPE) with 15-year UV inhibitor

Flammability: Highly Resistant (UL94HB)

LOAD CAPACITY

Up to 160,000 lbs (72,500 kg) depending on substrate

Compression Strength: 2,843 PSI (20 MPa) per ASTM D695-02A

SHIPPING INFORMATION

Available in 20-Mat or 30-Mat pallets

Standard 48 ft flatbed: 510 mats

20' Container: 200 GPM Mats & accessories

40' Container: 500 GPM Mats & accessories

Ground Protection Mats HS Code: 3926.90